

## FLAT SEAT (HARRIS STYLE) CUTTING TIPS

Hand torch Oxygen - Propane (LPG)



Hand torch Oxygen - Acetylene




Part No	Cutting Capacity	Oxygen kg/cm <sup>2</sup>
FT6290-000NX	0 - 5 mm	1 - 2
FT6290-00NX	5 - 10 mm	1.5 - 2
FT6290-0NX	10 - 15 mm	2 - 3
FT6290-1NX	15 - 25 mm	2.25 - 3.5
FT6290-2NX	25 - 50 mm	3 - 4
FT6290-3NX	50 - 75 mm	3 - 4.5
FT6290-4NX	75 - 150 mm	3.5 - 5.5
FT6290-5NX	150 - 200 mm	4.5 - 5.5
FT6290-6NX	200 - 300 mm	5 - 6.5

Part No	Cutting Capacity	Oxygen kg/cm <sup>2</sup>
FT6290AC-000	0 - 5 mm	1 - 2
FT6290AC-00	5 - 10 mm	1 - 2
FT6290AC-0	10 - 15 mm	1.5 - 2.5
FT6290AC-1	15 - 25 mm	2 - 3.5
FT6290AC-2	25 - 50 mm	3 - 4.5
FT6290AC-3	50 - 100 mm	3 - 4.5
FT6290AC-4	100 - 175 mm	3.5 - 5.5
FT6290AC-5	175 - 250 mm	4.5 - 5.5

Machine Torch Hi Speed Oxygen - Propane (LPG) Natural Gas



Part No	Cutting Capacity	mm / min Speed
FT6290VVC-00000	0 - 4 mm	550 - 750
FT6290VVC-0000	4 - 6 mm	520 - 700
FT6290VVC-000	6 - 9 mm	480 - 650
FT6290VVC-00	9 - 12 mm	450 - 630
FT6290VVC-0	12 - 20 mm	400 - 600
FT6290VVC-1	20 - 75 mm	250 - 480
FT6290VVC-2	75 - 100 mm	190 - 280
FT6290VVC-3	100 - 175 mm	150 - 180
FT6290VVC-4	175 - 200 mm	150 - 180



Made in U.S.A