

MIG CHAMP INVERTER WELDER



Picture with optional Trolley

Technical Specifications

Power Voltage:	AC240V± 15% 50/60Hz Single phase	
Input Current:	45A	
Effective Current:	26.6	
Power Rating:	10.8G KVA	
Current Adjustment Range:	MMA/1 - 250A MIG/30 - 250A	
Voltage Adjustment Range:	MIG/15.5 - 26.5V	
No Load Voltage:	56.5	
Welding Wire Diameter (mm):	0.6/0.8/0.9/1.0 Solid 0.9/1.0/1.2 Flux Cored 0.9/1.0/1.2 Alloy	
Duty Cycle 40°C:	MMA	35% @ 224 AMPS 100% @ 137 AMPS
	MIG	35% @ 250 AMPS 100% @ 148 AMPS
Efficiency:	85%	
Power Factor:	0.72	
Insulation Class:	F	
Protection Class:	IP21S	
Weight:	24 kgs	
Dimensions:	580 x 230 x 450 mm	

Features

- DC MMA
- Gas/Gasless MIG
- Spool size 5kg/15kg
- Euro Connect MIG Torch
- Voltage Regulator Device
- Spool Gun ready - 4 Pin

Part Number	Includes
IWS250CR	<ul style="list-style-type: none"> • Machine • ZMB24-3 Metre Torch • Lead Kit • 190AR Regulator
JSJRTOLLEY3	Optional: Trolley

Independent Wholesale Welding Supply pursue a policy of continuous research and development and therefore reserve the right to change the specification, design or price without prior notice.