



MIG 350 INVERTER WELDER

Separate Wire Feeder
MIG • MMA • TIG




Features

- Latest IGBT Inverter Technology
- MIG MAG Function
- MMA (Electrode Welding) DC+/DC- Function
- Scratch Start DC TIG Welding Function
- Stepless Voltage Control & Wire Feed Control at Wire Feeder
- Variable Inductance & Burn back Control
- Adjustable Crater Controls
- Gas Purge / Inch Wire Function
- 2T/4T Trigger Function
- Separate Wire Feeder with Geared 4 Roll Drive
- LED Volt & Meter Digital Display
- 10 Meter Interconnecting Cables
- Trolley with Pull Out Storage
- Voltage Regulator Device

Technical Specifications

Primary Input Voltage:	415V 3 Phase
Rated Power Supply Capacity:	14 KVA
Welding Current: MIG	50 - 350 AMPS
MMA	10 - 350 AMPS
Duty Cycles @ 40°C: MIG	40% @ 350 AMPS 100% @ 221 AMPS
MMA	40% @ 350 AMPS 100% @ 221 AMPS
Welding Voltage Range DC:	16.5 - 31.5V
Welding Wire Size:	0.6 > 1.2 mm Ferrous 0.9 > 1.2 mm Aluminium 0.8 > 1.2 mm Stainless 0.9 > 1.6 mm Flux Cores
Weight (Excluding Work Leads, Cylinder & Wire):	72 kgs
Dimensions:	1295 x 880 x 475 mm

Part Number	Includes
IWS350SWF	<ul style="list-style-type: none"> • Power Source • Separate Wire Feed Unit • 10 Metre Arc Lead Set • 195AR Argon Regulator • Profax TX400-3545-15 Torch 100% Duty Cycle • Trolley (Part Number JSTROLLEY)
TM26V-12-3558H	Optional: Tig Torch



TX400-3545-15
Euro 400 amp 15 Ft Gun



Tig Torch TM26V-12-3558H

Independent Wholesale Welding Supply pursue a policy of continuous research and development and therefore reserve the right to change the specification, design or price without prior notice.