

# PIRANHA 2 TUNGSTEN GRINDER

- Ideal for general shop use.
- Easy set up, optimal consistency and near perfect repeatability.
- Compact, durable and solid design with no vibration.
- Universal collet arm for 3 electrode sizes - with no equipment changes.
- Containment baffle to keep dust in.
- Electrode notching station for simple cut-off.
- Double sided grinding wheel.
- Angle Range: 10° - 60°
- Electrode Diameters: 1.0 MM, 1.6 MM, 2.4 MM
- Minimum Electrode Length: 19.05 MM
- Voltage: 100/120 VAC, 50/60HZ, 220V
- Power Consumption: 70 WATTS
- Motor: 1/10 HP, 8000 RPM, 1.5 AMPS
- Dimensions: 304.8 MM X 203.2 MM X 203.2 MM (LxWxH)
- Weight: 6.35 KGS



Part No	Description
PG2	Piranha 2 Tungsten Grinder

# PIRANHA 3 TUNGSTEN GRINDER



- Designed for commercial use.
- Continuous grinding of 1.0 MM - 4.8 MM tungsten.
- Solid steel construction with no vibration.
- Longitudinal grinding for maximum arc stability.
- Electrode guide accommodates 6 electrode sizes.
- Electrode notching station for simple cut off.
- Electrode guide has square end grind position.
- 15.24 CM diamond wheel improves surface finish.
- Vacuum port ready.
- Angle Range: 10° - 60°
- Electrode Diameters: 1.0 MM, 1.6 MM, 2.4 MM, 3.2 MM, 4.0 MM, 4.8 MM
- Minimum Electrode Length: 19.05 MM
- Voltage: 100/120 VAC, 50/60HZ, 220V
- Power Consumption: 500 WATTS
- Motor: 1/3 HP, 1680 RPM, 5 AMPS
- Dimensions: 508 MM X 304.8 MM X 304.8 MM (LxWxH)
- Weight: 23.13 KGS

Part No	Description
PG3	Piranha 3 Tungsten Grinder