

## RIDGE PURGE SYSTEM



### EZ PURGE SYSTEM

- Unique silicone ball design ensures air tight seal of pipe.
- For pipe diameters between 3/4" - 8" (19 mm - 203 mm).
- <0.1% oxygen levels achieved in under 2 minutes.
- Basic spine withstands up to 450°C.
- Cuts down purging gas and time.

Part No	Description
TMEZ00075	3/4" - 1" (20 - 25 mm) EZ Purge System
TMEZ0010	1" - 1.2" (26 - 31 mm) EZ Purge System
TMEZ0015	1.2" - 1.6" (32 - 40 mm) EZ Purge System
TMEZ0020	1.6" - 2" (41 - 50 mm) EZ Purge System
TMEZ0025	2" - 2.4" (52 - 61 mm) EZ Purge System
TMEZ0030	2.4" - 3" (62 - 74 mm) EZ Purge System
TMEZ0035	3" - 3.4" (75 - 85 mm) EZ Purge System

Part No	Description
TMEZ0040	3.4" - 4" (88 - 100 mm) EZ Purge System
TMEZ0045	4" - 4.3" (101 - 110 mm) EZ Purge System
TMEZ0050	4.7" - 5.3" (120 - 135 mm) EZ Purge System
TMEZ0055	5.5" - 6.1" (140 - 155 mm) EZ Purge System
TMEZ0060	5.7" - 6.5" (145 - 165 mm) EZ Purge System
TMEZ0075	7.5" - 8" (190 - 205 mm) EZ Purge System
TMEZ0080	7.6" - 8.5" (195 - 215 mm) EZ Purge System



### SILICONE DISC SYSTEM 120

- Achieve an air tight seal in straight pipes.
- For pipe diameters between 4" - 12" (101 - 300 mm).
- <0.1% oxygen levels achieved in under 3 minutes.
- Help achieve a uniform weld profile.
- Helps cut down purging gas and time.



### SILICONE DISC SYSTEM 180

- Achieve an air tight seal in seal in bend pipes and elbows.
- For pipe diameters between 1.5" - 6" (38 - 150 mm).
- <0.1% oxygen levels achieved in under 3 minutes.
- Help achieve a uniform weld profile.
- Helps cut down purging gas and time.



### SILICONE DISC SYSTEM 200

- Achieve an air tight seal in straight pipes and dome ends.
- For pipe diameters between 3/4" - 2" (20 - 51 mm).
- <0.1% oxygen levels achieved in under 3 minutes.
- Help achieve a uniform weld profile.
- Helps cut down purging gas and time.

Part No	Description
TMSDB120	Silicone Disc System 120

Part No	Description
TMSDB180	Silicone Disc System 180

Part No	Description
TMSDB200	Silicone Disc System 200