

PLASMAJET 2

• POWERFUL • SIMPLE

SEVERANCE CUT: 30 MM
QUALITY CUT: 25 MM

Product features:

- Powerful: 80 A with 40% at 40°C duty cycle.
- 3 steps to simplify the selection of the right current according to the thickness to be cut.
- Maximum quality and safety with the patented torch.
- Drag cutting up to 8 mm for maximum quality.
- Delivered ready to use.
- IP 23 for use on outdoor sites.
- 4 wheels and a strong design for intensive industrial use.



Technical Specifications	Plasmajet 2
Primary Input	
Input Voltage 3 ph	220 / 230 / 380 / 400V - 50/60 Hz
Max. Input Current	49 / 47 / 28.5 / 27 A
Output	
Cutting Current	30 - 50 - 80 A
Duty Cycle at 40°C	80 A at 40% 50 A at 80% 30 A at 100%
Compressed Air	5 bar - 180 l/min
Protection Index	IP 23
Insulation Class	H
Standards	EN 60974-1; EN 60974-7; EN 60974-10
Dimensions Characteristics	
Dimensions (L x W x H)	500 x 855 x 755 mm
Net Weight	80 kg

To Order	Plasmajet 2
Package Includes: Power Source, Torch 5m, 3m Earth Cable with Clamp, 5m Air Cable, 6m Primary Cable, 1 Set of Wear Parts	
W000261826	
To Order	JET CP 3.0
FL Electrode	W000302575
C Electrode	W000302576
L 1.2 Nozzle	W000302568
C 1.4 Nozzle	W000302524
Skirt TN	W000302630
Skirt TI	W000270053
Skate for Skirt TN	W000302609
Key Wrench	W000302578