

PRESTOJET 1

• MINIMUM WEIGHT • FLEXIBLE • CONVENIENT

SEVERANCE CUT: 10 MM
QUALITY CUT: 8 MM

Lightweight Prestojet provides cutting current up to 30 amps. The pressure is measured with an electronic sensor and the inverter technology allows low current consumption.

- Microprocessor control and digital display.
- Genuine cut up to 8 mm and severance cut up to 10 mm.
- Low air and current consumption.
- High operator safety.
- Light and easy to transport.
- Weight 8 kgs.
- Long nozzle and electrode for angle cutting.



Technical Characteristics	Prestojet 1
Primary Input	
Single Phase Input	230V +/- 10% - 50-60 Hz
Effective Consumption	14 A
Output	
Cutting Current	10 - 30 A
Duty Cycle at 40 °C	25 A at 60% 30 A at 35%
Compressed Air	4 bars - 100 l/min
Protection Index	IP 23
Insulation Class	H
Standards	EN 60974-1; EN 60974-7; EN 60974-10
Dimensions (LxWxH)	435 x 185 x 306 mm
Net Weight	8 kg

To Order	Prestojet 1
Package Part No includes: Power Source, Prestojet 1 Torch 4m, 3m Earth Cable with Clamp, Wear Parts, 3 m Primary Cable	W000277620
Torch CPT 800 - 4m	W000275097
To Order	Torch Parts CPT 800 - 4m
Electrode	W000274224
Diffuser	W000274266
0.65 Nozzle	W000274969
0.8 Nozzle	W000274265
TN skirt	W000274226
TI skirt	W000274225
Wrench	W000274862
Long Electrode	W000278629
0,8 Long Nozzle	W000278628