

PRESTOJET 2

THE POWER OF TECHNOLOGY

With its portability and high power, this unit is perfect for all maintenance operations. The duty cycle 40°C allows use for heavy duty operations, including automatic applications and gouging. The autolink feature and the digital display give the maximum flexibility together with top performance.

Product Features:

- High quality cut due to the patented SAF-FRO technology.
- Heavy duty cycle 50% at 40°C for intensive applications.
- Autolink function (automatic setting of the net supply 230V or 400V).
- Light, small and powerful.
- Easy to use due to the digital display.
- Gouging possibilities.



Technical Characteristics	Prestojet 2
Primary Input	
Input Voltage Three Phases	230V - 400V +/- 10% with autolink 50/60 Hz
Max. Input Current at 400V	15.5 A
Max. Input Current at 230V	14 A
Output	
Cutting Current	20 - 65 A
Duty Cycle at 40°C 400V	65 A at 60% 50 A at 100%
Duty Cycle at 40°C 230V	40 A at 100%
Compressed Air	5 Bars - 180 l/min
Protection Index	IP 23S
Insulation Class	H
Standards	EN60974-1; EN60974-7; EN60974-10
Dimensions (L x W x H)	435 x 235 x 380 mm
Weight	25 kg

To Order	Prestojet 2
Package Includes: Power Source, 5m Torch, 3m Earth Cable with Clamp, 5m Air Cable, Set of Wear Parts, 6m Primary Cable	W000272670
Torch CP 2.5 - 5 m	W000302639
To Order	Torch JET CP 2.5
FL Electrode	W000302575
L 1.2 Nozzle	W000302568
TN Skirt for Drag Cutting	W000302630
TN Skirt for Distance Cutting	W000302053
Wrench	W000302578