

PRESTOJET 4

• QUALITY • RELIABILITY

SEVERANCE CUT: 45 MM
QUALITY CUT: 40 MM



Product Features:

- Superior quality cut up to 35 mm.
- Compact design.
- Gouging position.
- Automatic re-start.
- Automatic version.
- Digital display and control of the parameters.
- 3 cutting modes: cutting - grid - gouging.

Technical Characteristics	Prestojet 4
Power Supply	400V 50/60 Hz \pm 15% Three Phase
Primary Consumption (I max)	40.3 A
Air Pressure and Flowrate	5.5 Bars - 180 l/min.
Duty Cycle 10 min. Cycle (at 40°C)	120 A at 60% 100 A at 100%
Dimensions (L x l x H)	720 x 235 x 380 mm
Net Weight	35 kg
Protection Class	IP 23

To Order	Prestojet 4
Package Includes: Power Source, 6m Primary Cable, 1 Torch JET CP 4.5 - 6 m Long, 1 Earth Cable with Clamp, Set of Wear Parts	W000262498
Air Cooled Torch JET CP 4.5 - 6m	W000302641
Air Cooled Torch JET CP 4.5 - 15m	W000302642
To Order	Wear Parts for Drag Cutting (1 - 8 mm)
Electrode FL	W000302575
Nozzle L 0.65 (1 - 3mm - 20A)	W000302623
Nozzle L 0.8 (1 - 4mm - 30A)	W000302569
Nozzle L 1.0 (1 - 6mm - 40A)	W000302567
Nozzle L 1.2 (1 - 8 mm - 60A)	W000302568
Skirt	W000302668
To Order	Wear Parts for Distance Cutting (1 - 40 mm)
Electrode C	W000302576
Nozzle C 1.0 (1 - 10mm - 40A)	W000302571
Nozzle C 1.2 (1 - 15mm - 60A)	W000302572
Nozzle C 1.4 (1 - 25mm - 85A)	W000302524
Nozzle C 1.6 (1 - 40mm - 120A)	W000302573
Skirt	W000302667
Skate	W000302666
Skirt with Crenels	W000271310
Conical Skirt (Beveling Skirt)	W000274878
To Order	Wear Parts for Gouging
Electrode L	W000302574
Nozzle G 2.2	W000302671
Skirt	W000302535
Skate	W000302673
Wrench	W000302578