

SAXOJET

• PORTABLE • EASY TO USE • HIGH QUALITY CUT

SEVERANCE CUT: 8 MM
QUALITY CUT: 4 MM

Product features:

- Quality cut 4 mm, Severance 10 mm.
- Built-in compressor: just plug and cut.
- Light and portable (12 kg).
- Input current < 16 A, can be used with a domestic plug.
- Digital display of parameters, friendly and easy interface.
- Delivered ready to use.
- Cuts without earth clamp up to 2 mm.



Technical Characteristics	Saxojet
Primary Input	
Single phase input	230 V - 50 - 60 Hz
Max. input	16 A
Output	
Cutting current	10 - 20 A
Duty cycle at 40°C	20 A at 50%
Protection index	IP 23
Insulation class	H
Standards	EN 60974-1; EN 60974-7; EN 60974-10
Dimensions Characteristics	
Dimensions (L x W x H)	435 x 185 x 306 mm
Net Weight	12 kg
Machine Part Number	W000263708

Technical Characteristics	Saxojet
To Order	Torch
Air-cooled 4 m torch CPT 800	W000275097
Torch body	W000274860
Wear parts for drag cutting:	
Electrode FL	W000274224
Diffuser	W000274266
Nozzle FL 0.65 (1 to 3 mm - 20 A)	W000274969
Nozzle FL 0.8 (1 to 10 mm - 30 A)	W000274265
Skirt TN	W000274226
Skirt TI	W000274225
Wear parts for angle cutting:	
Electrode long	W0002748629
Nozzle long Ø 0.8 (1 to 8 mm - 30 A)	W000278628
Wrench	W000274862