

STEPLESS CLAMPS



- Light weight
- High grade stainless steel
- 360° Stepless design - no steps or gaps on inner circumference
- Narrow band, concentrated seal compression
- Sensitive to soft neoprene or silicone tubing
- Smooth edged band steel prevents damage to hose
- Tamper detectable design

Part No	Description	Closed	Open
16702488	Stepless Clamp	5.3 mm	6.5 mm
16700001	Stepless Clamp	5.8 mm	7.0 mm
16700002	Stepless Clamp	6.8 mm	8.0 mm
16700003	Stepless Clamp	7.0 mm	8.7 mm
16700004	Stepless Clamp	7.8 mm	9.5 mm
16700005	Stepless Clamp	8.3 mm	10.0 mm
16700007	Stepless Clamp	8.8 mm	10.5 mm
16700008	Stepless Clamp	10.1 mm	11.8 mm
16700009	Stepless Clamp	9.8 mm	12.3 mm
16700010	Stepless Clamp	10.8 mm	13.3 mm
16700011	Stepless Clamp	11.3 mm	13.8 mm
16700013	Stepless Clamp	12.0 mm	14.5 mm
16700016	Stepless Clamp	13.2 mm	15.7 mm
16700017	Stepless Clamp	14.5 mm	17.0 mm
16700020	Stepless Clamp	15.3 mm	18.5 mm
16700022	Stepless Clamp	16.6 mm	19.8 mm
16700024	Stepless Clamp	17.8 mm	21.0 mm
16700026	Stepless Clamp	19.4 mm	22.6 mm
16700029	Stepless Clamp	20.9 mm	24.1 mm
16700033	Stepless Clamp	23.9 mm	27.1 mm

O-CLIPS



- For medium pressure.
- Rubber hose, plastic tubing, co-axial and other electrical cable, rope etc are all readily clamped with O-Clips.
- Widely used on air, fluid, gas and team lines in plant maintenance or OEM applications.
- Zinc plated steel.
- Packet of 100 O-Clips

Part No	Description
OET0507	O-Clip 5 - 7 mm
OET0709	O-Clip 7 - 9 mm
OET0911	O-Clip 9 - 11 mm
1113	O-Clip 11 - 13 mm
1315	O-Clip 13 - 15 mm
1517	O-Clip 15 - 17 mm
1518	O-Clip 15 - 18 mm
1720	O-Clip 17 - 20 mm
2023	O-Clip 20 - 30 mm
2327	O-Clip 23 - 27 mm
2528	O-Clip 25 - 28 mm
2831	O-Clip 28 - 31 mm
3437	O-Clip 34 - 37 mm