



WELDING POSITIONER

Will hold 409 kgs in the horizontal position and 227 kgs in the vertical position
 Note: C/G of load not be more than 150 mm from the centre of the turntable and 150 mm from the face of the turntable.

Technical Specifications

Capacity Vertical:	227 kg
Capacity Horizontal:	409 kg
Load Center of Gravity:	150 mm
Tilt:	Power
Tilt Angle (Degrees):	0 - 135
Tilt Angle Indicator:	N/A
Ground Capacity:	500 Amps
Grounding Device:	Brass
High Freq. Protection:	Yes
Volt/Ac:	115 or 230
Power Req. 115V:	10 Amp
Table Thickness:	22 mm
Table Diameter:	498 mm
Table Configuration:	3 & 4 - Slot
Optional Chucks:	WPC-12 & 16
Optional Grippers:	WPG-22
Table Height (Horizontal):	641 mm
Table Center Height (Vertical):	539 mm
Through Hole:	N/A
Table R.P.M:	0.4 - 4
Rotation Motor H.P:	1/6 H.P.
Variable Speed Rotation:	on panel
Foot Control:	Fwd./Rev.
Hand Pendant:	Optional
Anchor Points:	4
Levelling Bolts:	Included
Unit Width:	660 mm
Unit Length:	860 mm
Shipping Weight (Approx.):	264 kgs



Features

- 498 mm Diameter Table
- 0.4 to 4 rpm Rotation Speed
- Power Tilt Adjustment
- 230 Volt
- 0 - 135° Tilting Angle
- High Frequency Protected
- Standard Fwd/Rev. Foot Control
- Shipping Weight 264 kgs
- 1 Year warranty

Part Number	Includes
WP500-2	Machine and Foot Control